



Shown with Turf Tires

SPECIFICATIONS

Stock Code

All Terrain	70.4067 (1 kit per tractor)
Turf	70.4068 (1 kit per tractor)
Bar	70.4069 (1 kit per tractor)
Weight	80 lbs (36.25 kg) (per axle)
Additional Tractor Width	24 inches (12 inches/tire) (61 cm)

All specifications subject to change without notice or obligation

Note:

- (A) Do NOT use dual wheels when using the Ventrac VERSA-Loader.
- (B) Engine manufacturers' maximum angle of operation is 25° for continuous use (all directions) and 30° intermittent use*. The 4500P Kawasaki DFI is rated for 30° continuous use.
- (C) Do NOT use with Wheel Extensions

* Intermittent use is up to 10 minutes on the slope, then return to level ground before returning to the slope.

Dual Wheels are available for the 4000 series tractors. They are designed to increase stability, traction, and safety on slopes. Dual wheels are also great for reduction of soil compaction on delicate ground. Once the dual hubs have been installed on each wheel, the duals can be quickly mounted and dismantled.*

Duals are recommended for sandy soils or where a broad distribution of tractor weight is desired, including when driving sideways on slopes greater than 20 degrees (not to exceed 30 degrees).

Duals are only one of numerous considerations for safety on slopes; speed, terrain, irregularities, and stopping the unit are other serious factors to consider for safe operation of the tractor.

*Recommended tire pressure for dual wheels can be found in the 4500 operator manual and also on the sticker inside of the hood



Shown with Standard Tires

TRACTOR COMPATIBILITY KEY:



500 Venture Drive
Orrville, OH 44667
1.866.836.8722

Fax: 330.683.0000
www.ventrac.com
info@ventrac.com