

WINTER CAB	
Model	KW452
Stock Code	70.2014
Windshield Wiper	Standard
Mounts On	Standard Roll Bar
Easy Access Panel to Switches	Standard
Front & Rear Work lights	Standard
Maximum Slope with Cab	10° (18%)
Dimensions	
Overall Height	74 in. (188 cm)
Overall Length	59 in. (150 cm)
Overall Width	50 in. (127 cm)
Weight	385 lbs. (174 kg)
Height (installed on power unit)	81 in. (206 cm)
Height with Strobe Beacon (installed on power unit)	86 in. (219 cm)
Length (installed on power unit w/standard hitch)	92 in. (234 cm)

•	`	'	,	,	,		
Length (installed on p	ower unit w/stan	dard hitch)		92 in. (234	cm)		
Turning Radius (cab i	nstalled on powe	er unit)		68 in. (173	cm)		
Optional Accessories							
Mirror Kit				70.2006-	-4		
Defrost Fan Kit				70.2006-	-6		
Strobe Light Kit				70.8161			
Hazard Lights Kit				70.8162	2		
Windshield Washer K	it			70.8148	3		
Heater Kit for Kubota	tractors (4500Y)			70.2014-	51		
Heater Kit for Kawasa	aki tractors (4500	P)		70.8137	7		
Heater Kit for Kubota	tractors (4500Z)			70.2014-	53		
Lift Sling				47.0381			
All specifications subject to	change without notic	e or obligation	ı				



Designed to fit the Ventrac 4520 & 4500 tractors, the KW452 Cab offers exceptional visibility, while providing the operator with protection and comfort in many weather conditions.

NOTE:

- **A.** The KW452 weather cab cannot be used with the Ventrac KH500 Versa-Loader or RV602 Collection Vacuum.
- **B.** Do not operate on slopes over 10° when cab is installed.

STANDARD FEATURES

- · Dual Port USB Outlet for Device Charging
- · Optional windshield washer kit available
- · Operator Controls and Fuse Positioning for easier access
- · Intermittent Windshield Wiper Function
- · Rear Vent with Optional Wiper Function
- Roof Design to channel water away from side windows and any rear mounted accessories like the SA250
- · Better headroom clearance for operator
- · Improved hazard light kit
- · Breakaway LED strobe
- All heater kits now come standard with radiator baffle for improved heat output
- Simplified heater installation
- · Simplified integrated lift points



Easy Access to Switches and Fuse Panel




Exceptional Visibility and Interior Room



LED Work Lights, 2 Front and 1 Rear



Fully Sealed, Breakaway Mounted Optional Strobe Beacon



Better Headroom Clearance



3 Window Latches for Ventilation



Optional Defrost Fan



